



circuit breaker VL1250N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection trip unit ETU10, LI In=1250A, rated current IR=500...1250A, overload protection, II=1.25 to 10xIN, short-circuit protection without auxiliary release without auxiliary/alarm switch

Weight	26.74 kg
Net Weight	26.74 kg

General Product Approval	Test Certificates	other
--------------------------	-------------------	-------



[Special Test Certificate](#)



other	Dangerous goods	Environment
-------	-----------------	-------------

[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)

[Transport Information](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL7712-1SB36-0AA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL7712-1SB36-0AA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL7712-1SB36-0AA0
CAx-Online-Generator
<http://www.siemens.com/cax>
Information- and Downloadcenter (catalogues, leaflets,...)
<http://www.siemens.com/energy-automation>



last modified:

6/17/2023

