



### Main

Range of product	Modicon Quantum automation platform
Product or component type	Processor
Software name	Concept ProWORX 32
Processor name	80186
Mathematical coprocessor	Without

### Complementary

Clock frequency	20 MHz
Memory description	Internal RAM 368 kB
Exact time for 1 Kinstruction	0.3...1.4 ms LL984
Watchdog timer	250 ms
Clock drift	+/-8 s/day at 0...60 °C
I/O words	64 I/64 O remote 64 I/64 O max local 30 I/32 O distributed
I/O words/network	500 I/500 O distributed
Drops/Network	63 distributed
Number of drops	31 remote
Number of network	3 distributed 2 remote
Battery type	Lithium 7 µA 210 µA
Battery capacity	1.2 AH
Battery life	10 yr
Number of port	1 Modbus Plus 1 Modbus RS232
Communication module processor	2 NOM, NOE, CR, NMS
Switch function	Without key switch
Marking	CE
Bus current requirement	790 mA
Module format	Standard
Product weight	0.3 kg

### Environment

Product certifications	CUL FM Class 1 Division 2
Standards	CSA C22.2 No 142 UL 508
Resistance to electrostatic discharge	8 kV on air conforming to IEC 801-2 4 kV contact conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

## Contractual warranty


---

Period	18 months
--------	-----------

---

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots