

Product datasheet

Specifications



Unity processor - 8 racks (12 slots)
/ 16 racks (4/6/8 slots) - 1880 mA, 5
V DC

TSXP574634M

(!) Discontinued on: 31 Dec 2018

(!) End-of-service on: 18 Dec 2025

(!) Discontinued

EAN Code: 3595863811681

Main

Range of product Modicon Premium Automation platform

Product or component type Unity processor

Software designation Unity Pro

Complementary

Concept Transparent Ready

Number of racks 16 4/6/8 slots
8 12 slots

Number of slots 128
64
96

Discrete I/O processor capacity 2040 I/O

Analogue I/O processor capacity 256 I/O

Number of application specific channel 64

Number of process control channel 20 up to 60 simple loops

Integrated connection type Non isolated serial link female mini DIN connector (RS485) (19.2 kbit/s)
Ethernet TCP/IP RJ45 connector
USB port (12 Mbit/s)

Port Ethernet 10BASE-T/100BASE-TX

Communication module processor capacity 4
1
3
8

Memory description Internal RAM (with PCMCIA card) 2048 kB program
Internal RAM (with PCMCIA card) 440 kB data
Internal RAM (without PCMCIA card) 440 kB program and data
PCMCIA card 16384 kB additional data storage

Maximum size of object areas 32768 %Mi located internal bits
64 %KWi constant words located internal data
64 %MWi internal words located internal data
Unlimited (DFB and EFB function blocks) unlocated internal data
Unlimited (elementary and derived data) unlocated internal data

Application structure 1 fast task
64 event tasks
1 master task

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Execution time per instruction	0.039...0.057 µs Boolean without PCMCIA card 0.048...0.057 µs Boolean with PCMCIA card 0.054...0.073 µs word or fixed-point arithmetic with PCMCIA card 0.054...0.073 µs word or fixed-point arithmetic without PCMCIA card 0.55...0.63 µs floating points with PCMCIA card 0.55...0.63 µs floating points without PCMCIA card
Number of instructions per ms	11.4 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 11.4 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 15.75 Kinst/ms 100 % Boolean with PCMCIA card 15.75 Kinst/ms 100 % Boolean without PCMCIA card
System overhead	0.08 ms for fast task 1 ms for master task
Marking	CE
Local signalling	1 LED (green) for Ethernet TCP/IP port ready (RUN) 1 LED (green) for processor running (RUN) 1 LED (red) for collision detection (COL) 1 LED (red) for Ethernet TCP/IP port fault (ERR) 1 LED (red) for I/O module or configuration fault (I/O) 1 LED (red) for processor or system fault (ERR) 1 LED (yellow) for activity on TER or AUX terminal port (TER) 1 LED (yellow) for Ethernet link diagnostics (STS) 1 LED (yellow) for reception activity (RX) 1 LED (yellow) for transmission activity (TX)
Current consumption	1880 mA at 5 V DC
Module format	Double
Net weight	0.61 kg

Environment

Standards	CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group D 73/23/EEC IEC 61131-2 CSA C22.2 No 142 89/336/EEC 93/68/EEC CSA C22.2 No 213 Class I Division 2 Group C 92/31/EEC UL 508
Product certifications	BV RMRS ABS RINA LR DNV GL
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	9.5 cm
Package 1 Width	18.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	1.025 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension


Repair

No

Dimensions Drawings

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.